



DATA SHEET

revision date
24.06.2024

product code

20.01.10.00

Mobile Point CM/FH



Kasia



WEIGHT	120 kg
MAX. DIMENSIONS (WxHxD)	Approx. 750 x 1110 x 1000 mm
MAX. NUMBER OF USERS	1
MIN. WATER FLOW FEED	40 l/min
WATER INLET	EXT 3/4"
WATER OUTLET	EXT 1/2"
MAX. WORKING PRESSURE	25 bar
PRESSURE (FEED)	2-10 bar
MEDIUM TEMPERATURE RANGE	70° C
NOMINAL ENGINE POWER	3 kW
BASIC FREQUENCY	50/60 Hz
NOMINAL VOLTAGE	300-500 V
NUMBER OF PIECES IN THE PACKAGE	1
NUMBER OF PIECES ON THE PALLET	1



CLEANACCESS

FOOD HYGIENE EQUIPMENT



- Durable, hygienic housing that allows the device to be installed in production areas.
- Easy access to the device through the service door.
- Equipped with an inverter, which enables flexible operation of the device and reduces energy consumption.
- The housing protects against excessive wear of components.
- Equipped with protection against dry running and too low pressure on the unit supply.
- The bonding ties used as a permanent element for fastening cables and wires is detectable by a metal detectors or X-Ray devices.

MAINTENANCE

The non-return valve and filter should be checked at least once a month. Depending on the degree of wear, it is recommended to replace them at least once a year.

The Central Point should only be installed in locations where ambient temperature above 0°C is guaranteed. The equipment should be protected against temperatures below freezing, as this may cause water freezing in the system and its damage. If there is a known risk of temperature dropping below freezing, immediately remove all water from the system.