



DATA SHEET

Data Sheet number
09.24

Revision
number
v.2

Revision date
15.07.2025

Product code

as listed in the table

STAINLESS STEEL FOAM GENERATOR



40 l



80 l



MATERIAL	Stainless Steel housing (acid-resistant) and connections
CAPACITY	40L, 80L
WATER INLET	EXT 1/2"
WORKING PRESSURE	8 bar
NUMBER OF PIECES IN THE PACKAGE	1

- The Foam Generator consist of a pressure tank made of stainless steel acid-resistant, placed on wheels with a centrally placed filling hole on the upper bottom.
- There are two stub pipes to which the supply fittings are connected compressed air into the tank and out from tank, the cleaning agent which, together with compressed air, creates cleaning foam.



Code	Name	Number of pieces
01.02.10.12	HYGIENIC hose fittings EXT/INT - 10m	10 m
02.01.01.12	ULTRA HYGIENIC® ball valve 1/2" with SS protection	1 pc.
03.03.01.12 .OUT.27	Stainless Steel Nipple 1/2" 27 mm	1 pc.
03.03.38.12	Reduction nipple EXT thread 3/8 "— 1/2"	1 pc.
06.01.B.R	Wytwornica piany 40L z reduktorm powietrza	1 pc.
07.05.02.12	Teflon Seal	3 pcs.
07.06.65.150	Foaming Nozzle 1/2" with 65°/150 l/m	1 pc.
07.07.01.02.W	Nozzle protection for foaming 1/2" White	1 pc.
08.01.00.01	Champing ring	1 pc.
08.01.01.01.B	Suction Hose Blue	10 mb
AIR SZŻ GZ1/4" FI 12	Air female quick coupling GZ ¼" hose FI 12	1 pc.
AIR. SZM DN 7,2 FI 6	Air male quick coupling DN 7,2 for hose FI 6	1 pc.
PIPE 22X1,5 /1.4301	Pipe 22x1,5 /1.4301 polished	1 pc.

MAINTENANCE

The housing is made of stainless steel. Its anti-corrosion properties depend on the conditions in which the steel is used and its maintenance. Stainless steel products should be cleaned, dried and maintained with products intended for this purpose. Particular attention should be paid to the regime of cleaning for products used in an environment of high salinity or humidity to prevent sediments accumulation.