



DATA SHEET

Data Sheet number
35.23

Revision number
v.2

Revision date
15.07.2025

Product code

as listed in the table

REDUCTION AND EXTENDING CONNECTORS




1



2



3



4



5



MATERIAL

Stainless Steel

TEMPERATURE RANGE

-15°C / 70°C

MAX. WORKING PRESSURE (dedicated to CCS systems)

50 bar (seal dependent)

THREAD TYPE

BSP

NPT POSSIBLE THREAD NPT

YES



PRODUCT CODES

NO	CODE	THREADS	NAME	WEIGHT	PACKAGE INFO
1	09.00.34.12	$\frac{3}{4}$ " EXT — $\frac{1}{2}$ " INT	Reducing connector $\frac{3}{4}$ " EXT — $\frac{1}{2}$ " INT	21 g	1 foil
2	09.02.01.02	$\frac{1}{2}$ " EXT — $\frac{1}{2}$ " INT	Extending connector $\frac{1}{2}$ " EXT — $\frac{1}{2}$ " INT	29 g	1 foil
3	09.01.12.34	$\frac{1}{2}$ " EXT — $\frac{3}{4}$ " INT	Reducing connector $\frac{1}{2}$ " EXT — $\frac{3}{4}$ " INT	65 g	1 foil
4	09.00.12.38	$\frac{3}{8}$ " EXT — $\frac{1}{2}$ " INT	Reducing connector $\frac{3}{8}$ " EXT — $\frac{1}{2}$ " INT	32 g	1 foil
5	09.00.12.14	$\frac{1}{2}$ " EXT — $\frac{1}{4}$ " INT	Reducing connector $\frac{1}{2}$ " EXT — $\frac{1}{4}$ " INT thread	19 g	1 foil

- Solid, durable and hygienic.
- Repetable and precisely made in accordance with ISO standard.
- Thread NPT available on request.
- Recommended thread sealing with teflon, washer or thread locker.