



DATA SHEET

revision date
10.02.2023

code

09.XX.XX.XX.X

REDUCTION AND EXTENDING CONNECTORS



MATERIAL	Stainless Steel
TEMPERATURE RANGE	-15°C / 70°C
MAX. WORKING PRESSURE (dedicated to CCS systems)	50 bar (seal dependent)
THREAD TYPE	BSP
NPT POSSIBLE THREAD NPT	YES

PRODUCT CODES

NO	CODE	THREADS	NAME	WEIGHT	PACKAGE INFO
1	09.00.34.12	3/4" EXT – 1/2" INT	Reducing connector 3/4" EXT – 1/2" INT	21 g	1 foil
2	09.02.01.02	1/2" EXT – 1/2" INT	Extending connector 1/2" EXT – 1/2" INT	29 g	1 foil
3	09.01.12.34	1/2" EXT – 3/8" INT	Reducing connector 1/2" EXT – 3/8" INT	65 g	1 foil
4	09.00.12.38	3/8" EXT – 1/2" INT	Reducing connector 3/8" EXT – 1/2" INT	32 g	1 foil
5	09.00.12.14	1/2" EXT – 1/4" INT	Reducing connector 1/2" EXT – 1/4" INT thread	19 g	1 foil



- Solid, durable and hygienic.
- Repetable and precisely made in accordance with ISO standard.
- Thread NPT available on request.
- Recommended thread sealing with teflon, washer or thread locker.